

TRIMAX SM-2200


- Input Frequency 950 ~ 2150MHz via 75Ω F-Type Connector
- Digital measurement of strength (bar graph and numbers)
- Signal Lock Tone Alert, Signal Lock Indicator Light
- 3.5 Inch High Definition TFT LCD Screen
- On board QPSK Demodulator allows viewing of FTA channels
- Easy Satellite Manager with Easy OSD Navigation
- Supports Network Searching
- Internal Calculator for Angles of Azimuth, Elevation and Polarity
- Upgrade software via PC
- Fast charge LI-ION Battery (1950mA) Approx. 4Hrs usage
- Small and compact size - 9.5cm x 15.5cm x 6cm
- ONLY 0.53Kgs (530gm)



CHECK



FIND



VIEW

Specifications: TRIMAX SM2200		
LNB Tuner	Connector	F Type
Input	Frequency Range	950 ~ 2150MHz
	Signal Level	-65 ~ -25dBm
	LNB Supply	13/18VDC Max 400mA
	LNB Switch	22KHz
	DiSEqC	Ver 1.0
Demodulator	Front End	QPSK
	Symbol Rate	2 ~ 45Mbps
	SCPC & MCPC	YES
	Spectral Inversion	AUTO
System Resource	Processor	32bit
	SDRAM	16Mbyte
	FLASH	2Mbyte
	EEPROM	8Kbyte
	Video / Audio Decoder	MPEG-2
Data Rate		up to 15M bits/s
Resolution		720*576, 720*480
Video Format		PAL/NTSC/SECAM
Audio		MPEG-1
Audio Type		Mono
Interface	Serial Data	USB Type
Power Supply	Li-Ion Battery	1950mA
	Voltage	12.6VDC
	Charger	SMPS
Physical	Size	9.5 x 15.5 x 4.5 (cm)
	Weight	0.5Kg

Small and Compact - Makes it ideal for the installer.
Great for use with SELECTV, Optus D2, D1, C1 and C-band Satellite Dishes

DIGITAL Satellite Finder

